

Linx TT3



Has your date coding system reached the end of its shelf-life?

If you are spending too much time and money on an outdated coding system such as a hot stamp or roller coder, then it's time you upgraded to the Linx TT3.

The Linx TT3 thermal transfer overprinter gives you the perfect coding solution for flexible packaging materials. Printing high quality codes time after time, the Linx TT3 is easy to use and can even save you money.

The Linx TT3 sets a new standard for simple date and batch coding – ideal for printing variable information onto bags, pouches and flow wrap.

Lowest Ribbon Costs

- Clutchless bi-directional ribbon drive system – allows more prints per ribbon for lowest cost of coding and minimises the risk of ribbon breakages
- Standard ribbon length 600m – less frequent ribbon changes required

Simplest Ribbon System

- Simple ribbon changeover with cassette system – increases uptime
- Fitting ribbon to cassette couldn't be easier

Easiest to use

- Clear, simple colour touch screen enables easy code set up – error-free operation
- Standard code formats permit basic coding without the need of a PC

Highest Quality Print

- Full resolution 300dpi printhead for printing even the smallest characters, time after time




Track it together



Linx TT3

Dimensions (mm)

Controller Top Elevation



Controller Front Elevation



TT3 Printer



Ribbon Cassette



Performance

Printer

Unique solid-state clutchless bi-directional ribbon drive
Intermittent motion
Continuous motion
Printhead width and resolution
Print area - continuous and intermittent motion mode
Ribbon width
Ribbon save option
Maximum ribbon length
Print speed - intermittent motion mode
Print speed - continuous motion mode
Cable length between printer and controller
Print speeds and throughput are substrate, application and set-up dependent

LinxTT3

-
-
-
- 35mm, 300dpi, 12 dots/mm
- 32mm (W) x 30mm (L)
- 22mm, 33mm
- Interleaved mode
- 600 metres
- 50mm/sec - 200mm/sec
- 40mm/sec - 500mm/sec
- 3 metres

General features

- 5.7" QVGA (240 x 320) CSTN colour LCD
- Touch screen operator interface
- WYSIWYG print preview
- Ribbon consumption indicator
- Clutchless bi-directional ribbon drive
- Simple ribbon webbing

- 3 levels of password protection
- On-board diagnostics
- On-board memory
- Off-line set up and parameter storage
- Multiple operator languages

Programming and printing facilities

- Coder supplied with a range of standard code formats
- CLARISOFT for TT3 code design software (Windows 2000/XP/Vista)
- Full downloadable font support for Windows TrueType (including multiple languages and Unicode support)
- Fixed and variable text fields with user entry
- Flexible date/time formats
- Formats for shift coding

- Field orientation 0°, 90°, 180°, 270°
- Mirror image printing, image rotation
- Real time dock functions
- Auto best before date calculation and concession management
- Scaleable text including rotation, mirror and inverse printing
- User configurable drop down lists fields

Options

Standard bracket systems for integrating coder into intermittent and continuous motion packaging machinery

-

Ribbon range

Wax / Resin ink
Colours - black, metallic white (others on request)
Resin ink

-
-
-

Connections/interfacing for

External inputs (fully software configurable)
External outputs (fully software configurable)
RS232
USB memory stick support

3 PNP (print go, inhibit print, spare and quadrature encoder)
4 (2 relay, 2 PNP)

-
-

Services

Air supply
Power supply
Operating temperature

4-6 Bar, locally regulated
90-240VAC 50/60Hz
5° - 40°C

Regulatory approvals

MET NRTL
CE mark
FCC

-
-
-

Key • standard ◦ option

Linx operates a policy of continuous product improvement and reserves the right to change the specification of products without notice.

www.codal.com.tn



Track it together



6, Résidence Mougari, Cité 11 Décembre 35000 Boumerdes - ALGERIE

Tel : 00 213 (0) 24 81 88 86 - Fax : 00 213 (0) 24 81 87 86 - Email : oussama.codal@gnet.tn

Linx est une marque déposée de Linx Printing Technologies Ltd. CLARINET et CLARISOFT sont des marques déposées de Claricom Ltd. Windows est une marque déposée de Microsoft Corporation. ZPL est une marque déposée de Zebra Technologies. Codesoft est une marque déposée de Teklynx. © Linx Printing Technologies Ltd 2006.